

Rotarod ICSLA_ROT_001

Parameters and Metadata

Equipment manufacturer ICSLA_ROT_005_001 | v1.0

procedureMetadata

Req. Analysis: false

Req. Upload: true

Is Annotated: false

Options: Bioseb,

Experimenter ID ICSLA_ROT_007_001 | v1.0

procedureMetadata

Req. Analysis: false

Req. Upload: true

Is Annotated: false

Body weight ICSLA_ROT_004_001 | v1.0

simpleParameter

Req. Analysis: false

Req. Upload: false

Is Annotated: false

Unit Measured: g

Latency to fall ICSLA_ROT_001_001 | v1.1

seriesParameter

Req. Analysis: false

Req. Upload: true

Is Annotated: true

Unit Measured: s

Increments: 1, 3, 2,

Acceleration mode ICSLA_ROT_010_001 | v1.0

procedureMetadata

Req. Analysis: true

Req. Upload: true

Is Annotated: false

Options: starting speed 4-final 40,

Rod surface ICSLA_ROT_009_001 | v1.0

procedureMetadata

Req. Analysis: true

Req. Upload: true

Is Annotated: false

Options: Foam rubber,

First intertrial interval ICSLA_ROT_011_001 | v1.0

procedureMetadata

Req. Analysis: false

Req. Upload: true

Is Annotated: false

Unit Measured: min

Options: 15,

Rod diameter ICSLA_ROT_008_001 | v1.1

procedureMetadata

Req. Analysis: true

Req. Upload: true

Is Annotated: false

Unit Measured: cm

Options: 4.5,

Passive rotation ICSLA_ROT_003_001 | v1.3

seriesParameter

Req. Analysis: false

Req. Upload: true

Is Annotated: true

Increments: 2, 3, 1,

Options: yes, no,

Latency to fall mean ICSLA_ROT_002_001 | v1.1

simpleParameter

Req. Analysis: false

Req. Upload: false

Is Annotated: true

Unit Measured: s

Derivation: meanOfIncrements('ICSLA_ROT_001_001', 3)

Second intertrial interval ICSLA_ROT_012_001 | v1.0

procedureMetadata

Req. Analysis: false

Req. Upload: true

Is Annotated: false

Unit Measured: min

Options: 15,

Equipment model ICSLA_ROT_006_001 | v1.0

procedureMetadata

Req. Analysis: false

Req. Upload: true

Is Annotated: false

Options: LE 8200,
