Open Field HRWLLA_OFD_001

Purpose

The Open Field test is used to assess anxiety and exploratory behaviors. It is based on the natural tendency of an animal to explore and to protect itself using avoidance which translates to a normal animal spending more time in the periphery of the Open Field arena than in the center (the most anxiogenic area).

Experimental Design

Minimum number of animals: 7M + 7F

• Age at test: Week 52

• Sex: We would expect the results of this test to show sexual dimorphism

Procedure

- 1. Animals are transported to the testing room (or ideally an antechamber) and left undisturbed for 30 minutes before the test.
- 2. Ensure that lighting conditions are as desired (150-200 lux) and that all equipment is working correctly:
 - 1. If using a beam break system, ensure that beams are not interrupted before putting the mouse and if measuring vertical activity (rears), check that height of the infrared frame for rears is correctly set.
 - 2. If using a videotracking system, set detection parameters appropriate for the coat color of the mice.
 - 3. For analysis, each openfield arena is divided into a peripheral zone measuring 8 cm from the edge of the arena walls, and a central zone around 40% of the total surface of the arena.
- 3. Testing is conducted during the light phase of the cycle with 1 hour gap from the light/dark change. Testing should be conducted during the same period of day.
- 4. Wipe the apparatus clean and allow time for it to dry
- 5. Each mouse is placed in the middle of a peripheral zone of the arena facing the wall and allowed to explore freely the apparatus, with the experimenter out of the animal's sight.

If more than one mouse can be tested in parallel, in adjacent open field arenas and mice are video-tracked, it is important to ensure that the tracking of each mouse starts as soon as the mouse is released to make data comparable.

Males and females must be run in separate tests; ideally males are tested first, then followed by females

- 6. At the end of the 20 min run, animals are labeled (if necessary) and put back into their home cage.
- 7. After each run, any feces are removed and the arena is thoroughly wiped.
- 8. Analysis of the recording is done to measure the activity of each mouse in each of the zones per 5 minute bins.

Notes

- 1. Please ensure that the mice are not handled prior to the test, except handling for cage change.
- 2. Ear clipping should be done after the test if necessary .

Data QC

- 1. Verify total time of run.
- 2. Coherence between latency, number of entries and time in the center; e.g. it is not possible to have zero entries and have spent some time spent in the center.

Parameters and Metadata

Distance travelled - total HRWLLA_OFD_020_001 | v1.2

simpleParameter

Reg. Analysis: false Reg. Upload: false Is Annotated: true

Unit Measured: cm

Derivation: sumOfIncrements('HRWLLA OFD 005 001', 4)

......

Number of rears - total HRWLLA_OFD_021_001 | v1.3

simpleParameter

Req. Analysis: false Req. Upload: false Is Annotated: true

Derivation: sumOfIncrements('HRWLLA_OFD_006_001', 4)

Whole arena average speed series HRWLLA_OFD_002_001 v1.2 seriesParameter		
Req. Analysis: false	Req. Upload: false	Is Annotated: true
Unit Measured: cm/s		
Increments: 10, 5, 20, 15,		
Center average spesimpleParameter	eed HRWLLA_OFD_017_00	01 v1.0
Req. Analysis: false	Req. Upload: true	Is Annotated: true
Unit Measured: cm/s		
Latency to center estimpleParameter	entry HRWLLA_OFD_018_	001 v1.1
Req. Analysis: false	Req. Upload: true	Is Annotated: true
Unit Measured: s		

Arena Material HRWLLA_OFD_040_001 | v1.0

procedureMetadata

Req. Analysis: false	Req. Upload: false	Is Annotated: false
Experimenter ID HE procedureMetadata	RWLLA_OFD_035_001 v1.1	
Req. Analysis: false	Req. Upload: true	Is Annotated: false
Periphery distance travelled HRWLLA_OFD_010_001 v1.1 simpleParameter		
Req. Analysis: false	Req. Upload: true	Is Annotated: true
Unit Measured: cm		
Number of Rears HRWLLA_OFD_006_001 v1.1 seriesParameter		
Req. Analysis: false	Req. Upload: false	Is Annotated: true
Increments: 15, 20, 10, 5,		

Center distance travelled HRWLLA_OFD_014_001 | v1.1

simpleParameter

Req. Analysis: false	Req. Upload: true	Is Annotated: true
Unit Measured: cm		
Periphery average seriesParameter	speed series HRWLLA	A_OFD_043_001 v1.3
Req. Analysis: false	Req. Upload: false	Is Annotated: true
Unit Measured: cm/s		
Increments: 15, 10, 5, 20,		
Periphery resting t	ime HRWLLA_OFD_011_0	01 v1.1
Req. Analysis: false	Req. Upload: true	Is Annotated: true
Unit Measured: s		

Whole arena permanence HRWLLA_OFD_008_001 | v1.1

simpleParameter

Req. Analysis: false Req. Upload: true Is Annotated: false
Unit Measured: s

Central zone surface area HRWLLA_OFD_026_001 | v1.1

procedureMetadata

Req. Analysis: false Req. Upload: true Is Annotated: false

Unit Measured: % of total area

Options: 40, 39, 42, 41,

Arena ID HRWLLA_OFD_038_001 | v1.0

procedureMetadata

Req. Analysis: false Req. Upload: false Is Annotated: false

.....

Equipment model HRWLLA_OFD_025_001 | v1.0

procedureMetadata

Req. Analysis: true Req. Upload: true Is Annotated: false

Options: LE8822, TijmeOF9, ActiMot / MoTil 480 x 480 mm, 2325-0248, MED-OFA-RS, Unknown, ActiMot / MoTil, Opto-Varimex 4, VMX 1.4b, SuperFlex Fusion,		
Type of analysis HRWLLA_OFD_033_001 v1.1 procedureMetadata		
Req. Analysis: true	Req. Upload: true	Is Annotated: false
Options: Video tracking, Wide	e beam break,	
Center permanence time HRWLLA_OFD_016_001 v1.1 simpleParameter		
Req. Analysis: false	Req. Upload: true	Is Annotated: true
Unit Measured: s		
Height of the wall HRWLLA_OFD_030_001 v1.0 procedureMetadata		
Req. Analysis: false	Req. Upload: false	Is Annotated: false

Unit Measured: cm

Center average speed series HRWLLA_OFD_047_001 | v1.2 seriesParameter Req. Analysis: false Req. Upload: false Is Annotated: true Unit Measured: cm/s Increments: 5, 20, 15, 10, Number of center entries HRWLLA_OFD_019_001 | v1.1 simpleParameter Reg. Analysis: false Reg. Upload: false Is Annotated: true Light beam barrier height (Z axis) HRWLLA_OFD_049_001 | v1.1 procedureMetadata Req. Analysis: true Req. Upload: false Is Annotated: false Unit Measured: cm **Description:** height of the Z axis light beam used to determine when mouse is rearing Options: 8.6, 6.8, 8.0, 7.5,

Date equipment last calibrated HRWLLA_OFD_041_001 | v1.2

procedureMetadata

Req. Analysis: false Req. Upload: false Is Annotated: false

.....

Whole arena resting time HRWLLA_OFD_007_001 | v1.1

simpleParameter

Req. Analysis: false Req. Upload: true Is Annotated: true

Unit Measured: s

Start Time HRWLLA_OFD_037_001 | v1.1

procedureMetadata

Req. Analysis: false Req. Upload: false Is Annotated: false

.....

Periphery zone HRWLLA_OFD_032_001 | v1.2

procedureMetadata

Req. Analysis: false Req. Upload: true Is Annotated: false

Unit Measured: cm

Options: 7.9, 7.5, 7.35, 7.6, 8, 9.39,

Equipment manufacturer HRWLLA_OFD_024_001 | v1.1

procedureMetadata

Req. Analysis: true Req. Upload: true Is Annotated: false

Options: Accuscan, San Diego, Noldus, Biobserve, TSE Systems, O'hara CO Ltd.,

MED Associates Inc, Columbus Instruments, Panlab, Omnitech,

Arena Size HRWLLA_OFD_034_001 | v1.0

procedureMetadata

Req. Analysis: false Req. Upload: true Is Annotated: false

Options: 44x44, 40.5x40.5, 44.5x44.5, 45x45, 42x42, 50x50, 43.2x43.2, 40x40,

.....

Periphery permanence time series HRWLLA_OFD_042_001 | v1.2

seriesParameter

Req. Analysis: false Req. Upload: false Is Annotated: true

Unit Measured: s

Increments: 10, 5, 15, 20,

Disinfectant HRWLLA_OFD_036_001 | v1.1

procedureMetadata

Req. Analysis: false Req. Upload: false Is Annotated: false Center resting time series HRWLLA_OFD_045_001 | v1.3 seriesParameter Req. Analysis: false Req. Upload: false Is Annotated: true Unit Measured: s Increments: 20, 10, 5, 15, Periphery permanence time HRWLLA_OFD_012_001 | v1.1 simpleParameter Req. Analysis: false Req. Upload: true Is Annotated: true Unit Measured: s

Whole arena resting time series HRWLLA_OFD_001_001 | v1.1

Req. Analysis: false Req. Upload: false Is Annotated: true

Unit Measured: s
Increments: 15, 20, 10, 5,

Number of center entries series HRWLLA_OFD_048_001 | v1.1 seriesParameter

Req. Analysis: false Req. Upload: false Is Annotated: true

Increments: 20, 15, 10, 5,

Periphery distance travelled series HRWLLA_OFD_003_001 | v1.2

seriesParameter

Req. Analysis: false Req. Upload: false Is Annotated: true

Unit Measured: cm

Increments: 20, 15, 10, 5,

.....

Periphery resting time series HRWLLA_OFD_004_001 | v1.2

seriesParameter

Req. Analysis: false Req. Upload: false Is Annotated: true

Unit Measured: s

Increments: 10, 5, 20, 15,

Distance travelled HRWLLA_OFD_005_001 | v1.2

seriesParameter

Req. Analysis: false Req. Upload: true Is Annotated: true

Unit Measured: cm

Increments: 10, 20, 5, 15,

Color of arena HRWLLA_OFD_029_001 | v1.0

procedureMetadata

Req. Analysis: false Req. Upload: false Is Annotated: false

Options: White, Black, Transparent, Grey,

Center permanence time series HRWLLA_OFD_046_001 | v1.2

seriesParameter

Req. Analysis: false Req. Upload: false Is Annotated: true

Unit Measured: S		
Increments: 5, 20, 15, 10,		
	HRWLLA_OFD_015_001 v	/1.1
simpleParameter		
Req. Analysis: false	Req. Upload: true	Is Annotated: true
Unit Measured: s		
Porcontago contor	time upwelle off ood	004 14 0
simpleParameter	time HRWLLA_OFD_022_0	JU1 V1.2
Req. Analysis: false	Req. Upload: false	Is Annotated: true
Unit Measured: %		
Derivation: mul(div('HRWLLA	_OFD_016_001', 'HRWLLA_OI	FD_008_001'), 100)

Software Version HRWLLA_OFD_039_001 | v1.0

procedureMetadata

Req. Analysis: false Req. Upload: true Is Annotated: false

Options: TSE ActiMot Vers. 08.00, Versamax 4.2, TimeOFCR4, Topscan Lite,		
Activity Monitor V6.02, Opto-V	arimex 4 AutoTrack System 4.9	97, Ethovision XT v8.5,
Actitrack system, 06.15 / 07.0	1, Image OF, Fusion v6.3, Etho	vision XT v15,
Distance from light D_031_001 v1.1 procedureMetadata	t source: if direct ill	umination HRWLLA_OF
Req. Analysis: false	Req. Upload: false	Is Annotated: false
Unit Measured: cm		
Number of animals procedureMetadata	per cage HRWLLA_OF	D_028_001 v1.0
Req. Analysis: false	Req. Upload: false	Is Annotated: false
Equipment ID HRWLI procedureMetadata	LA_OFD_023_001 v1.0	
Req. Analysis: false	Req. Upload: true	Is Annotated: false

Whole arena average speed HRWLLA_OFD_009_001 | v1.1

simpleParameter

Req. Analysis: false	Req. Upload: true	Is Annotated: true
Unit Measured: cm/s		
Light intensity in th	ne centre of the are	na HRWLLA_OFD_027_001
v1.1 procedureMetadata		
Req. Analysis: false	Req. Upload: true	Is Annotated: false
Unit Measured: Lux		
	velled series HRWLLA	
Req. Analysis: false	Req. Upload: false	Is Annotated: true
Unit Measured: cm		
Increments: 20, 10, 15, 5,		

Periphery average speed HRWLLA_OFD_013_001 | v1.1

simpleParameter

Req. Analysis: false Req. Upload: true Is Annotated: true

Unit Measured: cm/s

.....

Percentage center movement time HRWLLA_OFD_050_001 | v1.0

simpleParameter

Req. Analysis: false Req. Upload: false Is Annotated: true

Unit Measured: %

Description: percentage_center_movement_time

Derivation:

mul(div(sub('HRWLLA_OFD_016_001', 'HRWLLA_OFD_015_001'),'HRWLLA_OFD_008_001'),100)

Resting definition threshold HRWLLA_OFD_051_001 | v1.0

procedureMetadata

Req. Analysis: false Req. Upload: false Is Annotated: false

Description: Parameter measuring how the equipment defines a 'resting' animal

Options: Stationary for > 1 second, Stationary for any time, Within grid for > 2 seconds,

Rearing definition threshold HRWLLA_OFD_052_001 | v1.0

procedureMetadata

Req. Analysis: false Req. Upload: false Is Annotated: false

Description: Parameter measuring how the equipment defines a 'rearing' animal

Options: No threshold, 1 second,